

# GUARDTECH REMOVER®



## CONCRETE REMOVER AND DEGREASER FOR RMC PLANT EQUIPMENT

- POWERFUL & EFFECTIVE**
- BIODEGRADABLE**

- DOES NOT DAMAGE SURFACES**
- SAFE & READY TO USE**

### PRODUCT DESCRIPTION

GTR® Premium is a new-generation stripping product developed to meet the latest regulations.

GTR® Premium is highly effective at removing concrete and cement residues and storage and demoulding oils.

GTR® Premium also works for hydraulic limes, anhydrite, plasters and other powdered.

GTR® Premium is less aggressive than other products on the market based on citric, hydrochloric and phosphoric acids, so it is safer to use. It has been designed to meet the varying requirements of applicators in terms of effectiveness, safety, use and impact on the environment.

### USE

Ideal for maintaining RMC equipment such as metal formwork, wooden mouldboxes, concrete skips, props, RMC plants, concrete mixer trucks, etc.

### CHEMICAL NATURE

Formulation based on organic compounds.

### ADVANTAGES AND CHARACTERISTICS

- Powerful stripper, more effective than hazardous acids.
- Applicable to all substrates with no major impact (metals, glass, rubber, paints, etc.).
- Does not damage spray guns.
- Non volatile.
- Non flammable.

### ENVIRONMENT

#### Ecological and respects the environment:

- No hydrochloric, phosphoric or sulphuric acid.
- VOCs < 1 g/L\*.
- More than 100% biodegradable after 28 days\*.
- **NO CMRs** (substances that are carcinogenic, mutagenic or toxic to reproduction) such as methoxyacetic acid.

\* Calculation based on the components' data.

## CONTAINERS

5 and 25 Kg containers.  
230 Kg drums.  
1000 Kg IBC containers.

## TECHNICAL DATA

Physical state at 20 °C	: Liquid
Colour	: Pale yellow
Odour	: Slight
pH	: 1.5 ± 0.5
Relative density	: 1.06± 0.02
Solubility in water [vol/vol]	: Total
Flashpoint [°C]	: Not applicable

## HOW TO USE

- It is essential to do tests first and to wear individual protective equipment.
- Use the product neat: do not dilute or mix with other products.
- Spray the product uniformly once or twice depending on the thickness. Time between each layer: 15 minutes minimum.
- Leave the product to act from 30 minutes to 12 hours (night work).
- Thoroughly rinse the treated surface using a high pressure washer.

## APPLICATION TOOLS

Apply with a low pressure sprayer.



## COVERAGE

Usage depends on the thickness of residue; thicker deposits may require more than one application. The following values are for guidance only:

**6 to 8 m<sup>2</sup>/ Kg.**

## CLEANING YOUR EQUIPMENT

Tools and equipment should be cleaned with water immediately after use.

## STORAGE

- Store in a dry place at a temperature of between 5°C and 30°C. Reversible product in case of frost.
- Shelf-life: 24 months from date of manufacture, in original unopened can.

## RECOMMENDATIONS

- Do not dilute or mix with other substances.
- Product can alter surfaces made of low-quality alloys and electro-galvanised materials. Always carry out a test first.
- For best results it is essential to use the product when the temperature of the substrates is above 5°C and below 30°C.
- Avoid applying during heavy rain or in very hot weather. Air temperature between 5°C and 30°C.

## HEALTH AND SAFETY

- Breathing protection: No breathing protection equipment is required under normal use conditions with suitable ventilation.
- Hand protection: Wear household rubber gloves.
- Skin protection: Wear protective clothing over exposed areas of skin.
- Eye protection: Wear protective goggles.
- In case of ingestion: Do not induce vomiting. Contact a doctor or specialist.

### FOR PROFESSIONAL USE ONLY



## TECHNICAL SUPPORT

### GUARD INDUSTRY

695B Rue de l'Hers - ZA de la Masquere

31750 ESCALQUENS • FRANCE

Tél: +33 (0)1.55.86.17.60 • Fax:+33 (0)1.48.58.16.89

E-mail : [contactus@guardindustry.com](mailto:contactus@guardindustry.com)

[www.guardindustry.com](http://www.guardindustry.com)

**Important:** The content of this documentation is based on our experience with the product. Guard Industry guarantees the quality of its products but expressly disclaims all liability if the user does not follow the recommendations and conditions of use of the products, especially but not exclusively in the case of faulty application, application by untrained personnel, use of products not compatible with Guard Industry products, or adverse weather conditions. For more information, consult the safety data sheet.

**For the most recent version of our data sheet, visit our website [www.guardindustry.com](http://www.guardindustry.com)**

Last updated : 20/02/2023